



Jl-111C IP indoor/outdoor camera 2MP - DOME

Video verification cameras provide the user and ARC with a visual confirmation of the alarm reason and show what is going on in the building. Any event is automatically recorded so the user is in the picture when something happens.

o [Declaration of conformity - Jl-111C \(PDF 251.44 kB\)](#)

Description

A big advantage is an easy installation of the cameras even without an advanced knowledge of IT technologies. They are fully integrated into the MyJABLOTRON application and cooperate with the JABLOTRON 100+ system through Cloud. The customer has thus all the information about his or her premises clearly available in one place.

The camera takes colour videos in HD or Full HD resolutions. In case of poor light conditions it switches to a night mode using IF (Infrared) lighting.

Basic function of the camera:

- o Video sequences
- o Video recording of 30 sec. before the event (eg. Alarm or arming) and 30 sec. after it.
- o It clearly shows what caused the event and what happened immediately afterwards.
- o The user can also request its creation from the MyJABLOTRON application.

- o Recording
- o Continuous video saving with an optional history (3 or 7 days).
- o A full history is at the user's disposal; he or she can check it any time to find out what happened in the building at a particular moment.

- o Live video
- o It can be started from the web or mobile versions of the MyJABLOTRON application.
- o At any time, the user can check what is going on in the building.

Under a normal internet connection, it takes ca. 10 sec. to connect to the camera.

Technical specifications

Powering by connector	12V DC Alternatively from PoE adapter - 48 V (according to the 802.3af norm)
Current consumption during the day (standby)	200 mA
Current consumption at night (with IR reflector)	350 mA
Pixels	2 Mpix

Resolution	1920 x 1080 pix
Frames per second	8
Lens	2.8 mm (view angle 115°)
Type of lens	M12
Sensor chip	1/2.8" CMOS
WDR - backlight compensation	120 dB
Lens alignment options	0°- 355°
Camera alignment options	Horizontally: 0°- 355° Vertically: 0° - 75°
Data transfer amount at 8 frames/sec	approx. 256 kbps/HD, approx. 512 kbps/FullHD
Communication interface	RJ-45 10M/100M Ethernet
IR reflector coverage	max. 30 m (12x IR LED)
IR reflector lighting angle	70°
IR reflector wavelength	850 nm
Environment	outdoor general
Operational temperature range (Dome)	-30 °C to +60 °C, max. humidity 95%
IP covering	IP67, IK10
Dimensions, weight	111 x 111 x 82 mm, 500 g
Complies with	EN 55032:2015, EN 50130-4:2011+A1:2014, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 50581:2012