

Desktop Intercom Paging Microphone with 7-inch Touch Screen



- Built-in 7 inch resistance touch screen
- With numeric and function keys interface
- Support multiple paging modes
- Support user-defined setting of time for call forwarding, no answer, call waiting
- Automatically supplied to adaptive devices

Specifications

Model	OTR7702A
Network Interface	Standard RJ45 input
Support Protocol	TCP/IP,UDP,IGMP (Multicast)
Audio Format	MP3
Sampling Rate	8K-48KHz
Transmission rate	100Mbps
Audio Mode	16 bit CD quality
Display Size	7-inch
Screen Resolution	800 x 480 Pixel
Screen Type	65K Color DGUS Screen
Keyboard Type	Virtual QWERTY Keyboard
Keyboard Input Type	Touch screen
Inscribed speaker impedance and power rating	4Ω,2W
THD	≤1%
Frequency response	80Hz~16KHz +1dB/-3dB
SNR	>65dB
PHONE OUT output impedance and power rating	16Ω,2mW
LINE OUT Output Level	1000mV Industry standard wire terminals
LINE OUT Output Impedance	470Ω
LINE IN Input Sensitivity	350mV Industry standard wire terminals
MIC Input Sensitivity (Unbalance)	10mV
Short-circuit input	Dry contact input
Short-circuit output	Max 1A/30VDC Dry contact input
Working Temperature	5°C~40°C
Working Moisture	20%-80%Relative humidity, without condensation

Working Consumption	≤6W
Power Input	~190-240V 50-60Hz (power adapter); DC24V/2A
Size	233 × 159 × 89 mm
Weight	1.2 kg

Product Picture

